

ICE QUEEN 85C

230 V / 50 Hz

SELF-CONTAINED GRANULAR ICE MACHINE

FEATURES CARACTERÍSTICAS

- ▶ **PRODUCES DRY GRANULAR ICE**
PRODUCE HIELO GRANULAR SECO
- ▶ **THE MOST EFFICIENT EVAPORATOR IN THE MARKET, LOW ENERGY CONSUMPTION AND HIGH ICE PRODUCTION**
EL EVAPORADOR MÁS EFICIENTE DEL MERCADO BAJO GASTO ENERGÉTICO, ALTA PRODUCCIÓN DE HIELO
- ▶ **EVAPORATOR WITHOUT GASKETS OR SEALS**
EVAPORADOR SIN JUNTAS DE ESTANQUEIDAD NI RETENES
- ▶ **STAINLESS STEEL AUGER WITH RESILIENT COATING TO MAXIMIZE LIFESPAN**
HUSILLO DE ACERO INOXIDABLE CON POSTERIOR TRATAMIENTO SUPERFICIAL PARA AUMENTAR SU VIDA ÚTIL
- ▶ **POWERFUL SPEED REDUCER ON TOP**
POTENTE REDUCTOR DE VELOCIDAD EN LA PARTE SUPERIOR
- ▶ **SMART FRONT VENTILATION SYSTEM (SFVS) ALLOWS BUILT-IN INSTALLATION OF THE UNIT**
EL SISTEMA INTELIGENTE DE VENTILACIÓN FRONTAL (SFVS) PERMITE LA INSTALACIÓN EMPOTRADA DE LA MÁQUINA
- ▶ **CLEANING SWITCH: DISCONNECTS THE COOLING SYSTEM WHILE CIRCULATING WATER WITH DESCALING PRODUCT (CALKIN OR SIMILAR)**
BOTÓN DE LIMPIEZA: DESCONECTA LA EL SISTEMA DE REFRIGERACIÓN AL RECIRCULAR EL AGUA CON EL DESINCRUSTANTE (CALKIN O SIMILAR)
- ▶ **EASI: EASY ACCESS FOR SERVICE & INSTALLATION. ALL PANELS CAN BE DISASSEMBLED SEPARATELY**
EASI: EASY ACCESS FOR SERVICE & INSTALLATION. FÁCIL ACCESO A CUALQUIER PUNTO YA QUE TODOS LOS PANELES PUEDEN SER DESMONTADOS DE FORMA INDEPENDIENTE
- ▶ **ON/OFF LIGHTED ROCKER SWITCH**
INTERRUPTOR LUMINOSO DE FUNCIONAMIENTO ON-OFF
- ▶ **TROPICALIZED MACHINES (T CLASS) / HEIGHT ADJUSTABLE LEGS FROM 105MM TO 155MM**
MÁQUINAS TROPICALIZADAS (CLASE T) / PATAS DE ALTURA AJUSTABLE DE 105MM A 155MM
- ▶ **NATURAL GAS R290 WITH VERY LOW GLOBAL WARMING POTENTIAL WHICH ALSO REDUCES THE ENERGY CONSUMPTION**
GAS NATURAL R290 CON MUY BAJO ÍNDICE GWP EL CUAL TAMBIÉN REDUCE EL CONSUMO ENERGÉTICO
- ▶ **STIF: STRONG INOX FABRICATION. SOLID STRUCTURE SUPPORTED IN 4 STEEL COLUMNS. AISI 304 STAINLESS STEEL BODY.**
STIF: STRONG INOX FABRICATION. SÓLIDA ESTRUCTURA SOBRE 4 COLUMNAS. CARROCERÍA EN ACERO INOXIDABLE AISI 304
- ▶ **STRONGEST DOOR OPENING SYSTEM PATENTED BY ITV. DOOR MADE IN STAINLESS STEEL AISI 304.**
SISTEMA DE APERTURA MÁS ROBUSTO DEL MERCADO. PUERTA HECHA EN ACERO INOXIDABLE. SISTEMA DE APERTURA Y AMORTIGUACIÓN PATENTADO POR ITV
- ▶ **AN ANTI-LIMESCALE FILTER IS ADVISED IN HARD WATER AREAS (WATER HARDNESS OVER 30 °fH).**
SE RECOMIENDA USAR UN FILTRO ANTICAL EN CASO DE AGUAS DURAS (AGUA CON DUREZA SUPERIOR A 30°fH)



									
		(Kg)	(Kg)	(Kg)	(Kg)		(mm)	(mm)	
IQ 85C A		95	94	20	20	Width	465	525	DRY GRANULAR ICE 20% RESIDUAL WATER CONTENT
IQ 85C W		92	88				595	645	
						Height	784	920	

* WITH LEGS 889/939 CON PATAS 889/939

ACCESSORIES ACCESORIOS

INCLUDED




NOT INCLUDED (OPTIONAL)







REAR VIEW
VISTA TRASERA



FRONTAL VIEW
VISTA FRONTAL



LEFT SIDE VIEW
VISTA LATERAL IZQUIERDA



* All measurements in mm.
* Todas las cotas en mm.

OPERATING CONDITIONS CONDICIONES DE TRABAJO


PRODUCTION 50Hz PRODUCCIÓN 50 Hz

±10% V

10°C/43°C

5°C/38°C

1 bar/6 bar



V	Hz	ph
230	50	1N



IQ 85C AIR COOLED

°C °F	10° 50°	15° 60°	21° 70°	30° 86°
10° 50°	95	92	86	77
21° 68°	98	94	88	79
32° 90°	85	80	72	65
43° 109°	72	66	57	49



IQ 85C WATER COOLED

°C °F	10° 50°	15° 60°	21° 70°	30° 86°
10° 50°	92	90	86	80
21° 68°	89	88	84	79
32° 90°	84	82	77	67
43° 109°	83	80	75	63

MODELS
MODELOS



IQ 85C A



758 2.586

470

3

1,5

10

10,8

3,9

559 1.907

58

63

0,33

IQ 85C W



758 2.586

385

3

1,5

10

10,5

20,5

559 1.907

58

63

0,33

Revendedor:

bret **tecnica**
baking technology!

2 YEARS
WARRANTY

Subject to certain limitations
and exclusions. Only spare parts.
Sujeto a limitaciones y exclusiones.
Solo piezas de repuesto.



Brettecnica - Equipamentos Indústria Alimentar, Lda.
Av. 19 de Maio, nº 4 - Pavilhão 4
2715-001 Pero Pinheiro - Portugal
(351) 219 259 305 • comercial@brettecnica.com